

# RETREAD SPECIFICATIONS



The specs listed below are a recommendation only. Buffing equipment can vary and, as such, the specs below should be verified for each different style of buffer. Buff profile should be verified using pilot skives of 3/32" across buffed tread surface.

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	in
11R22.5	DS20	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
11R22.5	DA30	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
215/75R17.5	DA31SP	559.0	22.0	160.0	6.30	6.00
225/70R19.5		711.0	28.0	180.0	7.09	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
235/75R17.5	DA31	660.0	26.0	180.0	7.09	6.75
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
315/80R22.5	DA32	762.0	30.0	240.0	9.45	9.00
385/65R22.5	DA33-WB	1067.0	42.0	310.0	12.20	11.75
315/80R22.5	DA34	762.0	30.0	230.0	9.06	9.00
11R22.5	DD60	1016.0	40.0	225.0	8.86	8.25
11R24.5		1016.0	40.0	225.0	8.86	8.25
295/75R22.5		660.0	26.0	225.0	8.86	9.00
285/75R24.5		813.0	32.0	225.0	8.86	8.25
11R22.5	DD61	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
225/70R19.5	DD62SP	813.0	32.0	190.0	7.48	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
11R22.5	DD63	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
11R22.5	DM50	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
11R22.5	DT40	660.0	26.0	210.0	8.27	8.25
11R24.5		660.0	26.0	210.0	8.27	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	210.0	8.27	8.25
11R22.5	DT41	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	210.0	8.27	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
11R22.5	DD65	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
11R22.5	DD66	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
385/65R22.5	DM35-WB	1067.0	42.0	306.0	12.05	11.75
425/65R22.5		1067.0	42.0	338.0	13.31	12.25

